
From: Sent: To: Cc: Subject:	Chen, Isaac Monday, December 14, 2015 8:46 AM Houston, Robert Bogdan, Silvia FW: NPDES Guideline Clarification (BP)
b(5)	

Chen, Isaac





From: Michael Petrinic [mailto:MPetrinic@Technip.Com]

Sent: Tuesday, December 08, 2015 4:52 PM

To: Houston, Robert; Angove, Sharon **Subject:** NPDES Guideline Clarification

Robert, Sharon,

Thank you for the call today, and helping me out with my project. I have included the specifications of my project (only relevant sections) that I currently have – pigging with filtered seawater treated with UV colorless dye only (only NPDES Toxicity Test approved chemicals will be used). We will like to pig with a chemical that could potentially be more toxic (AQUASWEEP SRC4132), but may be filtered with Bentonite Clay.

Our plan with this new chemical is to use a filtration skid subsea, connected to the DC41 PLETs (as indicated in the provided document). Since the entire operation will be subsea, we plan on conducting a toxicity test prior to using the chemical (based on the statement contained in the NPDES permit: "In cases where the discharge point for hydrostatic test water is subsea, such as the subsea end of a pipeline, and it is impractical to collect a sample at the discharge point, operators may collect a sample for this monitoring requirement prior to use of the fluid."). However, this toxicity test will not be of the pure chemical being injected — we will conduct a function test of the where we flow the chemical with seawater through the exact filtration skid in Houston, collect a sample from the discharge port, and conduct a toxicity test of this sample. Will this method be allowed and approved by the EPA under this permit?

Also I read in the NPDES permit that "Note: Discharges treated by bromide, chlorine, or hypochlorite are not required for toxicity tests" – what does this mean? My interpretation is if we use a toxic chemical (say Glutaraldehyde), and we inject any one of those chemicals, does that mean the toxicity test is not required for the Glutaraldehyde, or the discharge mixture?

If there is anything that may be confusing, please let me know. Thank you.

Regards,

Michael Petrinic

Subsea Pre-Commissioning Specialist

Technip USA Inc. – 11720 Katy Freeway, Houston, TX – 77079 USA - <u>www.technip.com</u> Tel (Direct): +1 281 249 8869 - Main: +1 281 870 1111

This email and any attached files ("Message") may contain confidential and/or privileged information. It is intended solely for the addressee(s). If you receive this Message in error, inform the sender by reply email, delete the Message and destroy any printed copy. Any unauthorized use, distribution, or copying of this Message or any part thereof is prohibited. Emails are susceptible to alteration. Neither Technip nor any of its affiliates shall be liable for the Message if altered or falsified nor shall they be liable for any damage caused by any virus that might be transmitted with this Message.